



Working hard to keep workers safe

1900 Enterprise Parkway Suite H  
Twinsburg OH, 44087  
Email: [Sales@rtisafety.com](mailto:Sales@rtisafety.com)  
Phone: (800) 254-2990 Local: (330) 405-5444  
Fax: (330) 487-5521

## CLASS II KEVLAR HARNESS

\*\*All Harnesses can be made for external or internal use, please specify when ordering\*\*

- Class II Kevlar Harness w/ D Ring
- Class II Kevlar Harness w/ Steel Ladder Hook & D Ring
- Class II Kevlar Harness w/ Yates Hook & D Ring

### AVAILABLE CUSTOMIZATION OPTIONS

- Center, left, OR right closures
- Internal OR external
- Attachments:
  - Ladder Hook
  - Positioning Hook
- Adjustable waist and leg straps for comfort
- Extra-large size available – up to 68” waist
- “A-Frame” prevents user from inverting during egress

### COMPONENTS & DATA

- Nylon Webbing 1 3/4”
  - 10,000# Tensile Strength
- Kevlar Webbing 1 3/4”
  - 10,000# Tensile Strength
  - Fire Rated at 860°F
- Standards for Safety:
  - NFPA 1983 – Life Safety Rope and Equipment for Emergency Services, 2022 Edition



\*\*This life safety harness meets the requirements of NFPA 1983 standard on life safety rope and equipment for emergency services, 2022 and the optional flame resistance requirements of NFPA 1983 Class II\*\*

\*\*Emergency services Class II Life Safety Harness in accordance with NFPA 1983-2022\*\*

\*\*For a complete list of certifications, or for further questions, please visit our website [www.ritsafetysolutions.com](http://www.ritsafetysolutions.com)\*\*